

SUBCHAPTER III—INTERIM MANDATORY
SAFETY STANDARDS FOR UNDER-
GROUND COAL MINES

**§ 861. Mandatory safety standards for under-
ground mines**

(a) Coverage; enforcement; review

The provisions of sections 862 through 878 of this title shall be interim mandatory safety standards applicable to all underground coal mines until superseded in whole or in part by improved mandatory safety standards promulgated by the Secretary under the provisions of section 811 of this title, and shall be enforced in the same manner and to the same extent as any mandatory safety standard promulgated under section 811 of this title. Any orders issued in the enforcement of the interim standards set forth in this subchapter shall be subject to review as provided in subchapter I of this chapter.

(b) Purpose; initiation of studies and research

The purpose of this subchapter is to provide for the immediate application of mandatory safety standards developed on the basis of experience and advances in technology and to prevent newly created hazards resulting from new technology in coal mining. The Secretary of the Interior in coordination with the Secretary shall immediately initiate studies, investigations, and research to further upgrade such standards and to develop and promulgate new and improved standards promptly that will provide increased protection to the miners, particularly in connection with hazards from trolley wires, trolley feeder wires, and signal wires, the splicing and use of trailing cables, and in connection with improvements in vulcanizing of electric conductors, improvement in roof control measures, methane drainage in advance of mining, improved methods of measuring methane and other explosive gases and oxygen concentrations, and the use of improved underground equipment and other sources of power for such equipment.

(Pub. L. 91-173, title III, §301, Dec. 30, 1969, 83 Stat. 765; Pub. L. 95-164, title II, §203, Nov. 9, 1977, 91 Stat. 1317.)

AMENDMENTS

1977—Subsec. (b). Pub. L. 95-164, §203(a), substituted “The Secretary of the Interior in coordination with the Secretary shall immediately initiate studies” for “The Secretary shall immediately initiate studies”.

Subsecs. (c), (d). Pub. L. 95-164, §203(b), struck out subsec. (c) which related to the modification of standards, and subsec. (d) which related to the applicability of section 553 of title 5 in cases where the provisions of sections 862 to 878 of this title had provided that certain actions, conditions, or requirements be carried out as prescribed by the Secretary or the Secretary of Health, Education, and Welfare.

EFFECTIVE DATE OF 1977 AMENDMENT

Amendment by Pub. L. 95-164 effective 120 days after Nov. 9, 1977, except as otherwise provided, see section 307 of Pub. L. 95-164, set out as a note under section 801 of this title.

EFFECTIVE DATE

Subchapter operative 90 days after Dec. 30, 1969, except to the extent an earlier date is specifically pro-

vided for in Pub. L. 91-173, see section 509 of Pub. L. 91-173, set out as a note under section 801 of this title.

§ 862. Roof support

(a) Roof control plan; contents; review; availability

Each operator shall undertake to carry out on a continuing basis a program to improve the roof control system of each coal mine and the means and measures to accomplish such system. The roof and ribs of all active underground roadways, travelways, and working places shall be supported or otherwise controlled adequately to protect persons from falls of the roof or ribs. A roof control plan and revisions thereof suitable to the roof conditions and mining system of each coal mine and approved by the Secretary shall be adopted and set out in printed form within sixty days after the operative date of this subchapter. The plan shall show the type of support and spacing approved by the Secretary. Such plan shall be reviewed periodically, at least every six months by the Secretary, taking into consideration any falls of roof or ribs or inadequacy of support of roof or ribs. No person shall proceed beyond the last permanent support unless adequate temporary support is provided or unless such temporary support is not required under the approved roof control plan and the absence of such support will not pose a hazard to the miners. A copy of the plan shall be furnished the Secretary or his authorized representative and shall be available to the miners and their representatives.

(b) Creation of dangers by roof falls

The method of mining followed in any coal mine shall not expose the miner to unusual dangers from roof falls caused by excessive widths of rooms and entries or faulty pillar recovery methods.

(c) Location and supply of roof support material; safety devices for roof work

The operator, in accordance with the approved plan, shall provide at or near each working face and at such other locations in the coal mine as the Secretary may prescribe an ample supply of suitable materials of proper size with which to secure the roof of all working places in a safe manner. Safety posts, jacks, or other approved devices shall be used to protect the workmen when roof material is being taken down, crossbars are being installed, roof bolt-holes are being drilled, roof bolts are being installed, and in such other circumstances as may be appropriate. Loose roof and overhanging or loose faces and ribs shall be taken down or supported. Except in the case of recovery work, supports knocked out shall be replaced promptly.

(d) Roof bolts

When installation of roof bolts is permitted, such roof bolts shall be tested in accordance with the approved roof control plan.

(e) Recovery of roof bolts

Roof bolts shall not be recovered where complete extractions of pillars are attempted, where adjacent to clay veins, or at the locations of other irregularities, whether natural or otherwise, that induce abnormal hazards. Where roof